


CAROTE

Utilizare, turatie recomandata



Tipuri si utilizari

	Material	Suprafata	Adancime de gaurire	Coadă	Otel < 900 N/mm ²	Inox < 1100 N/mm ²	Otel aliat < 1300 N/mm ²	Alama	Bronz	Fonta	Aluminiu	Mase plastice
	HSS	Blank			●			●	○	○	●	○
	HSS	Blank			●			●	○	○	●	○
	HSSE Co5	Blank			●	●	○	●	○	○	●	○
	HSS	TiAIN			●	●	○	●	○	○	●	○
	HSS	Blank			●			●	○	○	●	○
	HSSE Co5	Blank			●	●	○	●	○	○	●	○
	HSS	TiAIN			●	●	○	●	○	○	●	○
	HSS	Blank			●			●	○	○	●	○
	HSS	TiAIN			●	●	○	●	○	○	●	○
	HSSE Co5	Blank			●	●	○	●	○	○	●	○
	TC HM	Blank			●	●	●	●	●	○	●	○
	TC HM	Blank			●	●	●	●	●	○	●	○
	TC HM	Blank			●	●	●	●	●	○	●	○
	TC HM	Blank			●	●	●	●	●		●	○
	TC HM	Blank			●	●	●	●	●	○	●	○

Turatie recomandata pentru carote HSS

Material		otel nealiat pana la 700 N/mm ²	otel aliat pana la 1000 N/mm ²	Fonta peste 250 N/mm ²	Aliaj CuZn casant	Aliaj CuZn rezistent	Aluminiu aliat cu pana la 11% Si	Termo- plactice	Plastice dure
Vc = m/min		30	20	10	60	35	30	20	15
Agent de racire		Ulei de taiere	Ulei de taiere	Aer comprimat	Aer comprimat	Aer comprimat	Ulei de taiere	Apa	Aer comprimat
Ø mm	Ø Zoli	turatie, rpm	turatie, rpm	turatie, rpm	turatie, rpm	turatie, rpm	turatie, rpm	turatie, rpm	turatie, rpm
12.0	15/32	796	531	265	1592	929	796	531	398
13.0	33/64	735	490	245	1470	857	735	490	367
14.0	35/64	682	455	227	1365	796	682	455	341
15.0	19/32	637	425	212	1274	743	637	425	318
16.0	5/8	597	398	199	1194	697	597	398	299
17.0	43/64	562	375	187	1124	656	562	375	281
18.0	45/64	531	354	177	1062	619	531	354	265
19.0	3/4	503	335	168	1006	587	503	335	251
20.0	25/32	478	318	159	955	557	478	318	239
21.0	53/64	455	303	152	910	531	455	303	227
22.0	7/8	434	290	145	869	507	434	290	217
23.0	29/32	415	277	138	831	485	415	277	208
24.0	15/16	398	265	133	796	464	398	265	199
25.0	63/64	382	255	127	764	446	382	255	191
26.0	1 1/32	367	245	122	735	429	367	245	184
27.0	1 1/16	354	236	118	708	413	354	236	177
28.0	1 3/32	341	227	114	682	398	341	227	171
29.0	1 9/64	329	220	110	659	384	329	220	165
30.0	1 3/16	318	212	106	637	372	318	212	159
31.0	1 7/32	308	205	103	616	360	308	205	154
32.0	1 17/64	299	199	100	597	348	299	199	149
33.0	1 19/64	290	193	97	579	338	290	193	145
34.0	1 11/32	281	187	94	562	328	281	187	141
35.0	1 3/8	273	182	91	546	318	273	182	136
36.0	1 27/64	265	177	88	531	310	265	177	133
37.0	1 29/64	258	172	86	516	301	258	172	129
38.0	1 1/2	251	168	84	503	293	251	168	126
39.0	1 17/32	245	163	82	490	286	245	163	122
40.0	1 37/64	239	159	80	478	279	239	159	119
41.0	1 39/64	233	155	78	466	272	233	155	117
42.0	1 21/32	227	152	76	455	265	227	152	114
43.0	1 11/16	222	148	74	444	259	222	148	111
44.0	1 47/64	217	145	72	434	253	217	145	109
45.0	1 25/32	212	142	71	425	248	212	142	106
46.0	1 13/16	208	138	69	415	242	208	138	104
47.0	1 55/64	203	136	68	407	237	203	136	102
48.0	1 57/64	199	133	66	398	232	199	133	100
49.0	1 15/16	195	130	65	390	227	195	130	97
50.0	1 31/32	191	127	64	382	223	191	127	96
51.0	2	187	125	62	375	219	187	125	94
52.0	2 3/64	184	122	61	367	214	184	122	92
53.0	2 3/32	180	120	60	361	210	180	120	90
54.0	2 1/8	177	118	59	354	206	177	118	88
55.0	2 5/32	174	116	58	347	203	174	116	87
60.0	2 3/8	159	106	53	318	186	159	106	80

Turatie recomandata pentru carote cu tais tratat

Material		otel nealiat pana la 700 N/mm ²	otel aliat pana la 1000 N/mm ²	Fonta peste 250 N/mm ²	Aliaj CuZn casant	Aliaj CuZn rezistent	Aluminiu aliat cu pana la 11% Si	Termo- plactice	Plastice dure
Vc = m/min		50	35	40	60	40	60	45	40
Agent de racire		Ulei de taiere	Ulei de taiere	Aer comprimat	Aer comprimat	Aer comprimat	Ulei de taiere	Apa	Aer comprimat
Ø mm	Ø Zoli	turatie, rpm	turatie, rpm	turatie, rpm	turatie, rpm	turatie, rpm	turatie, rpm	turatie, rpm	turatie, rpm
12.0	15/32	1327	929	1062	1592	265	1592	1194	1062
13.0	33/64	1225	857	980	1470	245	1470	1102	980
14.0	35/64	1137	796	910	1365	227	1365	1024	910
15.0	19/32	1062	743	849	1274	212	1274	955	849
16.0	5/8	995	697	796	1194	199	1194	896	796
17.0	34/64	937	656	749	1124	187	1124	843	749
18.0	45/64	885	619	708	1062	177	1062	796	708
19.0	3/4	838	587	670	1006	168	1006	754	670
20.0	25/32	796	557	637	955	159	955	717	637
21.0	3/4	758	531	607	910	152	910	682	607
22.0	7/8	724	507	579	869	145	869	651	579
23.0	13/16	692	485	554	831	138	831	623	554
24.0	15/16	663	464	531	796	133	796	597	531
25.0	63/64	637	446	510	764	127	764	573	510
26.0	1 1/32	612	429	490	735	122	735	551	490
27.0	1 1/16	590	413	472	708	118	708	531	472
28.0	1 3/32	569	398	455	682	114	682	512	455
29.0	1 9/64	549	384	439	659	110	659	494	439
30.0	1 3/16	531	372	425	637	106	637	478	425
31.0	1 7/32	514	360	411	616	103	616	462	411
32.0	1 17/64	498	348	398	597	100	597	448	398
33.0	1 19/64	483	338	386	579	97	579	434	386
34.0	1 11/32	468	328	375	562	94	562	422	375
35.0	1 3/8	455	318	364	546	91	546	409	364
36.0	1 27/64	442	310	354	531	88	531	398	354
37.0	1 29/64	430	301	344	516	86	516	387	344
38.0	1 1/2	419	293	335	503	84	503	377	335
39.0	1 17/32	408	286	327	490	82	490	367	327
40.0	1 37/64	398	279	318	478	80	478	358	318
41.0	1 39/64	388	272	311	466	78	466	350	311
42.0	1 21/32	379	265	303	455	76	455	341	303
43.0	1 11/16	370	259	296	444	74	444	333	296
44.0	1 47/64	362	253	290	434	72	434	326	290
45.0	1 25/32	354	248	283	425	71	425	318	283
46.0	1 13/16	346	242	277	415	69	415	312	277
47.0	1 55/64	339	237	271	407	68	407	305	271
48.0	1 57/64	332	232	265	398	66	398	299	265
49.0	1 15/16	325	227	260	390	65	390	292	260
50.0	1 31/32	318	223	255	382	64	382	287	255
51.0	2	312	219	250	375	62	375	281	250
52.0	2 3/64	306	214	245	367	61	367	276	245
53.0	2 3/32	300	210	240	361	60	361	270	240
54.0	2 1/8	295	206	236	354	59	354	265	236
55.0	2 5/32	290	203	232	347	58	347	261	232
60.0	2 3/8	265	186	212	318	53	318	239	212
61.0	2 13/32	261	183	209	313	52	313	235	209
65.0	2 9/16	245	171	196	294	49	294	220	196
68.0	2 43/64	234	164	187	281	47	281	211	187
70.0	2 3/4	227	159	182	273	45	273	205	182
71.0	2 51/64	224	157	179	269	45	269	202	179
75.0	2 61/64	212	149	170	255	42	255	191	170
80.0	3 5/32	199	139	159	239	40	239	179	159
85.0	3 11/32	187	131	150	225	37	225	169	150
90.0	3 35/64	177	124	142	212	35	212	159	142
95.0	3 47/64	168	117	134	201	34	201	151	134
100.0	3 15/16	159	111	127	191	32	191	143	127

